

Elmo Rietschle Products



Side Channel Blowers

- Vacuum up to : 800 mbar
- Pressure to +1000 mbar
- Flows from 16 to 1850 m³/hr



Liquid Ring Pumps

- Vacuum up to 33 mbar Abs
- Pressure to 2.6 bar
- Flows from 10 to 600 m³/hr



Rotary Vane Pumps

- Vacuum up to 0.1 mbar abs
- Pressure to 1.5 bar
- Flows from 4 to 1535 m³/hr



Claw Pumps

- Vacuum up to 60 mbar abs
- Pressure to 2.2 bar
- Flows from 60 to 1200 m³/hr

ROBUSCH®
PUMPS AND BLOWERS




ROBOX
evolution

- Vacuum up to -500 mbar
- Pressure to +1000 mbar
- Flows from 142 to 6120 CFM



PROTECT 5
Extended Warranty for GD Compressors



L Series: L07 - L22, L55-L140

- Fully Integrated Airend
- High Efficiency Drive
- Available in IE3 as well as IE4 motor
- Low Noise Levels
- Delcos Pro Controller till L22; Delcos XL Controller in L55 - L140
- Upto 46 °C Ambient
- Factory-Filled Lubricant
- A Range of Compressed Air Systems to Suit All Applications
- High Quality Rotary Screw Compressor

Li Series: Li30 - Li45

- The New Generation
- High Efficiency Airend
- Maximum Durability
- Belt Free Drive
- Energy Efficient Motor
- Intelligent Control
- Designed for Serviceability
- High Performance Separator
- Heavy Duty Inlet Filter



PROTECT 5
Extended Warranty for GD Compressors

PureAir - Ultima, Quantima, D Series, DH Series

- Oil Free compressor from 15kw to 355kw
- Innovative Oil-Free Compressors
- ISO Class: Zero Plus Silicone Free
- Highest Efficiency Levels
- Low Noise Design
- LP & HP Airends Individually Driven
- Very Efficient Heat Recovery
- Outstanding Energy Savings of up to 25% Easily Achievable
- High Performance Separator
- Connected with iConn Smart Flow Management



Downstream Equipment



- Refrigerant Air Dryers, Dessicant Air Dryers, Medical Dryers and Compressed Air Filters
- Refrigerant Air Dryers With Low Pressure Drop, Designed For Tropical Conditions
- Excellent Serviceability and Reliability
- Dessicant Air Dryers Used For Heatless Dryer Requirement
- Digital Display Showing Detailed Function of Dryer
- Purge Economizer As Standard Feature
- Separate Fill & Drain of Dryer Ports, Ease of Dessicant Replacement
- Medical Dryers For Guaranteed Dew Point Performance
- Air Quality As Mandated By NFPA99
- Bacterial Penetration Up to 0.0001%

Technical Data - Compressor Range

Model	Power (kW)	Capacity (CFM)	Max Operating Pressure Bar (g)
L07	7.5	46	7.5
L07	7.5	38	10
L 07	7.5	30	13
L 11	11	66	7.5
L 11	11	57	10
L 11	11	47	13
L 15	15	96	7.5
L 15	15	80	10
L 15	15	64	13
L 18	18.5	115	7.5
L 18	18.5	97	10
L 18	18.5	83	13
L 22	22	130	7.5
L 22	22	114	10
L 22	22	92	13

Your **Ultimate** Source
for Pressure and Vacuum

Technical Data - Compressor Range

Model	Power (kW)	Capacity (CFM)	Max Operating Pressure Bar (g)
L 23	22	147	7.5
L 26	26	171	7.5
L 29	30	195	7.5
Li 30	30	204	7.5
Li 30	30	201	8.5
Li 30	30	174	10
Li 37	37	249	7.5
Li 37	37	220	8.5
Li 37	37	218	10
Li 45	45	283	7.5
Li 45	45	248	8.5
Li 45	45	246	10
L 45+	45	306	7.5
L 45+	45	261	10
L 55	55	380	7.5
L 55	55	337	10
L 55	55	292	13
L 75	75	488	7.5
L 75	75	440	10
L 75	75	370	13
L 75+	75	520	7.5
L 75+	75	433	10
L 90	90	620	7.5
L 90	90	550	10
L 90	90	480	13

Technical Data - Compressor Range

Model	Power (kW)	Capacity (CFM)	Max Operating Pressure Bar (g)
L 110	110	738	7.5
L 110	110	662	10.5
L 110	110	576	13
L 132	132	812	7.5
L 132	132	755	10.5
L 132	132	660	13
L160	160	1133	7.5
L200	200	1387	7.5
L250	250	1485	7.5
L290	250	1664	7.5
Reciprocating Model	Power (HP)	Capacity (CFM) / Max Pressure (psig)	Air Receiver litre
GD 2340F 3	3.0	8.65/175	150
GD 2475C 5	5.0	13.99/175	225
GD 2475C 7.5	7.5	17.77/175	225
GD 2545D 7.5	7.5	24.18/150	300
GD 2545D 7.5	7.5	24.18/150	300
GD 2545D 10	10.0	30.00/175	300
GD 2545E 10	10.0	30.00/175	500
GD 2545E 12.5	12.5	35.00/175	500
GD 7100E 15	15.0	42.91/125	500
GD 15TE 20	20.0	59.80/125	500
GD 15TE 25	25.0	79.20/125	500
GD 15TE 25	25.0	79.20/125	500
High Pr Recip Model	Motor hp	Free Air Delivery cfm at Working Pressure 350 psig	500 psig
GD 7T2 Package	12.5	-	21.60
GD 15T2 Package	20.0	-	37.70
GD 15T2 Duplex Pkg	40.0	-	75.40
GD 15T Package	20.0	50	-
GD 15T Duplex Pkg.	40.0	100	-

* Date measured and stated in accordance with ISO1217 Annex C & Pneurop/Cagi PN2CPTC2 and at the following conditions:
Air Intake Pressure - 1 bar a/14.5 psia
Air Intake Temperature - 20°C/68°F
Humidity - 0% (dry)

Please Contact

CT CREATIVE TRADERS

Vapi : Shop No. 111-122, Heena Arcade,
Nr. GIDC Char Rasta, Vapi 396191. M: 98797 28891, 98962 94985
E: info@creativetraders.in W: www.creativetraders.in



CompAir Serving Industries

Compressors

- General Manufacturing
- Petrochemical/Chemical
- Food & Beverage
- Mining & Construction
- Oil & Gas
- Pharmaceutical/Medical/Environmental
- Automotive
- Power Generation

Blowers & Vacuum Pumps

- Water & Waste Water Treatment
- Surface Cleaning
- Food & Non Food Packaging
- Food & Beverage
- Plastics
- Medical
- Central Vacuum
- Construction
- Bulk Material Transfer
- Printing & Paper Handling

... and many more.

Gardner Denver Engineered Products India Pvt. Ltd.
Ahmedabad - 382220, Gujarat

www.gardnerdenver.com/industrials

AUTHORISED DISTRIBUTOR

CT CREATIVE TRADERS

M: 98251 19815, 98797 78191
E: info@creativetraders.in
W: www.creativetraders.in